

### C-1100 STAR III TANK

7, 15, 30 GALLON  
Heavy Duty 0.30" wall



#### Features:

- Extra heavy 0.30" thick wall polyethylene with UV inhibitors.
- Ships complete with the C-1100 pump model of your choice.
- 3 tank capacities to choose from: 7, 15, and 30 gallons.
- Molded-in threaded inserts and raised shelf for sturdy pump mounting.
- Lid positions include open, closed and vent.
- All necessary accessories are included.
- Convenient space saving rectangular shape.
- Raised off the floor for easy wash down.

#### Specifications:

Material: .....LLDPE  
Capacity: .....7, 15, or 30 U.S. Gallons  
Max. fluid temperature: .....130° F (54° C)  
Max. ambient temperature: ..14° to 110° F/ -10° to 43° C  
Approximate shipping wt: ...(includes C-1100V pump)  
7 gallon units = 26 lb. (11.8 kg)  
15 gallon units = 34 lb. (15.4 kg)  
30 gallon units = 40 lb. (18.1 kg)

#### Materials of Construction:

##### Tank system only:

Tank: .....Natural Polyethylene (LLDPE)  
Suction Strainer assembly:  
Tubing: .....Clear PVC  
Weight: .....Ceramic  
Footvalve adapter & body: PVDF  
Strainer screen: .....Polypropylene  
Check Ball: .....Ceramic  
Spring: .....Hastelloy C-276  
Ball Seat O-ring: .....TFE/P (optional EP)  
Static Seal O-ring: .....Viton<sup>®</sup> (optional EP)Natural  
Lid: .....Polypropylene  
Lid fasteners: .....Polypropylene

