

Blue-White®

Peristaltic & Diaphragm Metering Pumps for Aquatics

Choose the **METERING PUMP** Capabilities
Your Application Requires:



C-600P

C-1500N

A-100N

A1A

Flow Output Range	1–21.5 GPH (4–81.4 LPH)	.2–9.5 GPH (.5–36 LPH)	.35–95.1 GPH (.054–15 LPH)	.01–100 GPH (.01–15.8 LPH)
PSI	125 PSI (8.6 bar)		100 PSI (6.9 bar)	40 PSI (2.76 bar)
Enclosure Rating	NEMA 1 (IP20)	NEMA 3R (IP23)		NEMA 4X
Standards	NSF/ANSI 50, CE, ETL, CSA, ROHS			NEMA 4XNSF/ANSI 50, CE, CETLUS, ROHS
Control Methods	MANUAL			
Power Supply	100 TO 240VAC-50/60HZ			
Motor	AC SHADED POLE			BRUSHLESS DC

Whether it's a public swimming pool or a large water park attraction, maintaining optimal water chemistry requires the right balance of effective disinfection, swimmer comfort, and efficient maintenance. Blue-White FLEXFLO® and CHEM-FEED® metering pumps deliver the precision and reliability needed to keep aquatic facilities safe, clear, and operating at their best.



Learn more about Our
Dosing Pumps for Aquatics at www.blue-white.com

