
Exploded View and Parts List

EXPLODED VIEW



ltem	Catalog Number	Description	Qty
1	F-452004N	Union Nut (Nylon)	2
2	F-452330N	2.0" Adapter FNPT (PSF)	2
3	F-452002	Float Stop (PSF)	2
4	F-452043N	O-Ring (Viton)*	2
5	-	Float (PTFE)	2
6	-	Meterbody (PSF)	1

PARTS LIST

 Shading indicates item not sold separately

 *EP Option Available
 PSF= polysulfone

METER SPECS

Scale	Permanent dual scale silkscreen
Max Pressure	See Temperature vs. Pressure chart*
Max Temperature	See Temperature vs. Pressure chart*
Height	18-7/8 in. (479.4 mm)
Width	4-5/8 in. (117.5 mm)
Accuracy	± 2% of full scale reading

APPLICATION NOTES

Although meters may be suitable for other chemicals, Blue-White cannot guarantee their suitability. It is the responsibility of the user to determine the suitability of the flowmeter in their application. **Flowmeters are tested and calibrated for water only.**

MAINTENANCE

The "Exploded View" drawing illustrates assembly of the F-462N series meter. If your flowmeter needs to be cleaned refer to this drawing when reassembling the unit. The tapered tube may be cleaned with a soft bottle brush. Use a MILD soap and water solution for cleaning purposes. Note the float's "up" position.