

FLEXFLO®

PERISTALTIC METERING PUMPS

Choose the FLEXFLO® Capabilities Your Application Requires:



M1

M2

M3

M4

M5

Flow Output Range

.0001–5.6 GPH
(.004 – 21.2 LPH)

.0085–21.23 GPH
(.032–80.4 LPH)

.0002–33.3 GPH
(.0007–126 LPH)

.0028–158.5 GPH
(.01–600 LPH)

.0076–534 GPH
(.0286–2021 LPH)

Turndown

10,000:1

200:1

10,000:1

Warranty

5 YEAR

Variable Speed DC Motor

BRUSHLESS

BRUSH

BRUSHLESS

TFD (Pat.#7,001,153 and 7,284,964)

YES

YES

YES

YES

YES

Maintenance Mode(Pat. Pend)

NO

YES

YES

YES

YES

Motor Reverse

NO

YES

YES

YES

YES

Tube Info Button

NO

TIMER

REVOLUTION COUNTER & TIMER

Input: Remote Start/Stop

YES

YES

YES

YES

YES

Input: 4-20mA

YES

YES

YES

YES

YES

Input: Frequency (Pulsed)

NO

YES

YES

YES

YES

Output: Relay & CC

YES

YES

YES

YES

YES

Output: 4-20mA

YES

YES

YES

YES

YES

Output: Pulse

NO

NO

YES

YES

YES

Password Protect (PIN)

NO

NO

YES

YES

YES

Ethernet/IP™

NO

NO

YES

YES

YES

Profibus

NO

NO

YES

YES

YES

Modbus-TCP

NO

NO

YES

YES

YES

NSF 61 Listed

YES

YES

YES

YES

YES

FLEXFLO® PERISTALTIC PUMPS have smooth, quiet pumping action and deliver accurate amounts of chemical to your system. Four FlexFlo® models are offered featuring a broad range of output rates, electronics options and features. If you don't see the FlexFlo® pump that meets your system requirements, please contact the factory. Blue-White® specializes in meeting OEM requirements.

FLEXFLO® APPLICATIONS INCLUDE

Municipal Water Treatment
Municipal Wastewater Treatment
Chemical Injection
Chlorination
Chloramination
Fluoridation

Pac Injection
Acid Injection
Caustic Injection
Alum Injection