Blue-White®

FLEXFLO®

PERISTALTIC METERING PUMPS

Choose the FLEXFLO® Capabilities Your Application Requires:

	A1	A2	A3	A4	A5
Flow Output Range	.001–5.6 GPH (.002 – 21.2 LPH)	.02–21.23 GPH (.07–80.4 LPH)	.001–33.3 GPH (.003–126.1 LPH)	.01–158 GPH (.04–600 LPH)	.0498–540 GPH (.1884-2044 LPH)
Turndown	2,000:1	100:1	2,500:1		
Warranty	2 YEAR				
Variable Speed DC Motor	BRUSHLESS	BRUSH	BRUSHLESS		
TFD (Pat.#7,001,153 and 7,284,964)	YES	YES	YES	YES	YES
Maintenance Mode (Pat. #8,215,931)	NO	YES	YES	YES	YES
Motor Reverse	NO	YES	YES	YES	YES
Tube Info Button	NO	TIMER			
Input: Remote Start/Stop	YES	YES	YES	YES	YES
Input: 4-20mA	YES	YES	YES	YES	YES
Input: Frequency (Pulsed)	NO	YES	YES	YES	YES
Output: 4-20mA	YES	Optional	YES	YES	YES
Output: Pulse	NO	NO	YES	YES	YES
Password Protect (PIN)	NO	NO	YES	YES	YES
Industrial Ethernet (IP)	NO	NO	YES	YES	YES
Profibus	NO	NO	YES	YES	YES
Modbus-TCP	NO	NO	YES	YES	YES

FLEXFLO® PERISTALTIC PUMPS have smooth, quiet pumping action and deliver accurate amounts of chemical to your system. Four FLEXFLO® models are offered featuring a broad range of output rates, electronics options and features. If you don't see the FLEXFLO® pump that meets your system requirements, please contact the factory. Blue-White® specializes in meeting OEM requirements.

FLEXFLO® APPLICATIONS INCLUDE

Chemical Metering
Chlorination
Chloramination
Fluoridation
Polymer Injection
Pulp and Paper Slurries
Printing Inks
Oil Based Fluids
Gaseous Fluids
Shear Sensitive Fluids
Caustics
Chemical Slurries
Food and Beverage