

Blue-White®

FLEXFLO® Peristaltic Metering Pumps

Choose the **FLEXFLO®** Capabilities
Your Application Requires:



	A1	A2	A3	A4	A5
Flow Output Range	.003–5.6 GPH (.011–21.2 LPH)	.02–21.23 GPH (.07–80.4 LPH)	.001–33.3 GPH (.003–126.1 LPH)	.01–158 GPH (.04–600 LPH)	.0302–534 GPH (.1144–2021 LPH)
Turndown	2,000:1	100:1		2,500:1	
PSI	100 PSI (6.9 bar)		125 PSI (8.6 bar)		65 PSI (4.4 bar)
Warranty	2 YEAR				
Variable Speed DC Motor	BRUSHLESS	BRUSH		BRUSHLESS	
TFD (Pat.#7,001,153 and 7,284,964)	✓	✓	✓	✓	✓
NEMA 4X Enclosure	✓	✓	✓	✓	✓
Motor Reverse	■	✓	✓	✓	✓
Tube Info Button	■			TIMER	
Input: Remote Start/Stop	✓	✓	✓	✓	✓
Input: 4-20mA	✓	✓	✓	✓	✓
Input: Frequency (Pulsed)	■	✓	✓	✓	✓
Output: 4-20mA	✓	OPTIONAL	✓	✓	✓
Output: Pulse	■	■	✓	✓	✓
Password Protect (PIN)	■	■	✓	✓	✓
Industrial Ethernet (IP)	■	■	✓	✓	✓
Profibus	■	■	✓	✓	✓
Modbus-TCP	■	■	✓	✓	✓

FLEXFLO® PERISTALTIC PUMPS have smooth, quiet pumping action and deliver accurate amounts of chemical to your system. Four FLEXFLO® models are offered featuring a broad range of output rates, electronics options and features. If you don't see the FLEXFLO® pump that meets your system requirements, please contact the factory. Blue-White® specializes in meeting OEM requirements.

FLEXFLO® APPLICATIONS INCLUDE

Chemical Metering	Oil Based Fluids	Chemical Slurries
Chlorination	Gaseous Fluids	Coagulation
Chloramination	Shear Sensitive Fluids	De-Chlorination
Fluoridation	Caustics	Corrosion Inhibitors
Polymer Injection		



Learn more about
FLEXFLO® at www.blue-white.com

