Blue-White®

CHEM-FEED® DIAPHRAGM METERING PUMPS



Flow Output Range	.02-16.5 GPH (.09-62.5 LPH)	.3-40 GPH (.1154 LPH)	.0008-8.0 GPH (.0030-30.3 LPH)	.03-52.6 GPH (.10-199 LPH)
Turndown	100:1	100:1	10,000:1	1,000:1
Warranty	2 YEAR		5 YEAR	
Variable Speed DC Motor	BRUSH	BRUSH	BRUSHLESS	
Dia-Flex® PVDF Single-layer Diaphragm	Ø	Ø	•	Ø
DFD (Diaphragm Failure Detection)	Ø	Ø	•	Ø
Protective LCD Snap-on Cover	Ø	Ø	•	
Maintenance Mode	•	•		Ø
Input: Remote Start/Stop	Ø	Ø	•	Ø
Input: 4-20mA	Ø	Ø	•	Ø
Input: Frequency (Pulsed)	Ø	Ø	•	Ø
Output: 4-20mA	•	OPTIONAL	•	Ø
Proportional Dosing		•	•	Ø
Password Protect (PIN)			LOCKOUT BUTTON	Ø

CHEM-FEED® DIAPHRAGM METERING PUMPS provide superior chemical resistance, precision chemical metering capabilities, and are designed to provide excellent service in a wide range of applications.

CHEM-FEED® APPLICATIONS INCLUDE

Chemical Metering Pulp and Paper Slurries
Chlorination Printing Inks
Chloramination Oil Based Fluids
Fluoridation Gaseous Fluids
Polymer Injection Shear Sensitive Fluids

Caustics Chemical Slurries Food and Beverage



