

# For Conversion from the **FLEXFLO® A-100** to **FLEXFLO® A-100N**

## for Discontinued **MODEL A-100**

## use Replacement **MODEL A-100N**

Model Number	Output GPD	Max PSI		Model Number	Output GPD	Max PSI
A-130-4 (spa)	1.5	25	REPLACE WITH →	A1N00A-4T	2.3	100
A-130-6 (spa)	4.9	25	REPLACE WITH →	A1N10A-4T	4.9	100
A-145-6N (spa)	4.0	25	REPLACE WITH →	A1N10A-4T	4.9	100
A-114-4	6.0	25	REPLACE WITH →	A1N00A-6T	6.8	100
A-114-4N	6.0	25	REPLACE WITH →	A1N00A-6T	6.8	100
A-130-4	15.0	25	REPLACE WITH →	A1N10A-6T	16.0	100
A-130-4N	15.0	25	REPLACE WITH →	A1N10A-6T	16.0	100
A-114-6	22.0	25	REPLACE WITH →	A1N20A-6T	24.0	100
A-114-6N	18.0	25	REPLACE WITH →	A1N20A-6T	24.0	100
A-114-7	28.0	25	REPLACE WITH →	A1N30A-6T	30.1	75
A-114-7N	23.0	25	REPLACE WITH →	A1N20A-6T	24.0	100
A-130-6	49.0	25	REPLACE WITH →	A1N10A-7T	52.5	50
A-130-6N	40.0	25	REPLACE WITH →	A1N10A-7T	52.5	50
A-130-7	74.0	25	REPLACE WITH →	A1N20A-7T	76.1	50
A-130-7N	60.0	25	REPLACE WITH →	A1N20A-7T	76.1	50
A-145-6	74.0	25	REPLACE WITH →	A1N20A-7T	76.1	50
A-145-6N	60.0	25	REPLACE WITH →	A1N20A-7T	76.1	50
A-145-7	112.0	25	REPLACE WITH →	A1N30A-7T	95.1	50
A-145-7N	92.0	25	REPLACE WITH →	A1N30A-7T	95.1	50